# cementin Holding

#### SAFETY DATA SHEET

Product Name: D-Carb cement (CEM II A-LL 52.5 N) Page: 1/7

Date of Issue: 28 May 2025 Rev. No.: 01

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1. Product identifier

Product name: D-Carb cement (CEM II A-LL 52.5 N)
Product identifier: General Purpose Limestone Cement

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application: Binder for natural and artificially processed aggregates, such as sand,

gravel and pebbles, for production of mortar, plaster and concrete.

1.3 Details of the supplier of the safety data sheet

Supplier: AALBORG PORTLAND MALAYSIA SDN BHD

Lot 75244, Pinji Estate, P.O.Box 428,

30750 Ipoh, Perak, Malaysia

Tel: 05-382 0388

<u>aalborg@aalborgportland.com.my</u> www.aalborgportland.com.my

Responsible for safety data

sheet authoring:

aalborg@aalborgportland.com.my

Australia contact details: AALBORG PORTLAND AUSTRALIA PTY. LTD. ACN

Company: 106514201

68 Gosport Street, Hemmant, QLD 4174, Australia.

Contact No.: Phone: Toll Free 1800 953 661

Office: +61 7 3880 4128

Email: Sales@aalborgportland.com.au
Website: www.aalborgportland.com.au
Mr. John Drakes M. Mahila (1961) 448,749,703

Contact Person: Mr. John Prokos M. Mobile (+61) 418 719 793

#### 1.4 Emergency telephone number

Australia Poisons Information Centre 13 11 26

New Zealand Poison Information Service 0800 POISON (0800 764 766)

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture

The product is classified:

GHS: Eye Irrit. 2;H319 – Skin Irrit. 2;H315 – STOT SE 3;H335 - STOT RE 2;H373

Human health: Dust may irritate throat and respiratory system and cause coughing.

Frequent inhalation of dust over a long period of time increase the risk of developing lung diseases. Dust or splashes from the mixture may cause permanent eye damage. Dust has an irritating effect on moist skin. Prolonged

contact with wet cement/mixture may cause burns.

Environment: The product is not expected to be hazardous to the environment. In the

presence of water the product hardens to a solid mass which is not

biodegradable.



Product Name: D-Carb cement (CEM II A-LL 52.5 N)

Page: 2/7

Date of Issue: 28 May 2025 Rev. No.: 01

#### 2.2 Label elements





**WARNING** 

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

P260 Do not breathe dust.

P280 Wear protective gloves, eye and face protection.

P305/351/338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/attention.

P501 Dispose of contents/container in accordance with local regulations

Contains: Calcium oxide. When mixed with water it will form calcium

hydroxide which has a corrosive effect on skin and eyes.

2.3 Other hazards

Other hazards Not relevant.

#### **SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

#### 3.1 Mixtures

The product contains: Cement

The following substances shall be indicated according to legislation:

GHS:

%:	CAS-No.:	EC No.:	REACH	Chemical	Hazard classification:	Notes:
60-100	65997-15-1	266-043-4	Reg. No.:	name: Portland Cement	Skin Irrit. 2;H315 Eye Irrit. 2;H319 Skin Sens.1;H317 STOT SE 3; H335	
Below reporting limits	14808-60-7	273-761-1	-	Total Respirable Silica	Skin Irrit. 2;H315 Eye Irrit. 2;H319 Skin Sens.1;H317 STOT SE 3; H335	

### **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures

Inhalation: Move injured person into fresh air and keep person calm under observation.

If uncomfortable: Seek hospital and bring these instructions.

Skin contact: Remove contaminated clothing immediately and wash skin with soap and

water. In case of rashes, wounds or other skin disorders: Seek medical

attention and bring along these instructions.

Eye contact: Do not rub eye. Immediately flush with plenty of water for up to 15 minutes.

Remove any contact lenses and open eyelids widely. If irritation persists: Continue flushing during transport to hospital. Bring these instructions.



Product Name: D-Carb cement (CEM II A-LL 52.5 N)
Page: 3/7

Date of Issue: 28 May 2025 Rev. No.: 01

Ingestion: Immediately rinse mouth and drink plenty of water or milk. Keep person under

observation. Do not induce vomiting. If vomiting occurs, keep head low.

Transport immediately to hospital and bring along these instructions.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms/effects: See section 11 for more detailed information on health effects and

symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Not known.

**SECTION 5: FIREFIGHTING MEASURES** 

5.1 Extinguishing media

Extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

5.2 Special hazards arising from the substance or mixture

Specific hazards: Water used for fire extinguishing, which has been in contact with the

product, may be corrosive.

5.3 Advice for firefighters

Protective equipment for fire

fighters:

Selection of respiratory protection for fire-fighting: follow the general fire

precautions indicated in the workplace.

In case of contact with water used for fire extinguishing, use chemical

resistant protective suit.

**SECTION 6: ACCIDENTAL RELEASE MEASURES** 

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: Avoid inhalation of dust. Avoid contact with eyes and prolonged skin

contact. Use work methods which minimize dust production.

6.2 Environmental precautions

Environmental precautions: The product should not be dumped in nature but collected and delivered

according to agreement with the local authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up: Remove spillage with vacuum cleaner. If not possible, collect spillage with

shovel, broom or the like.

**SECTION 7: HANDLING AND STORAGE** 

7.1 Precautions for safe handling

Safe handling advice: Observe good chemical hygiene practices. Avoid spreading dust. Avoid

inhalation of dust. Avoid contact with eyes and prolonged skin contact.

Change contaminated clothing.

Technical measures: Use work methods which minimise dust production.

Technical precautions: Mechanical ventilation may be required. Provide easy access to water

supply and eye wash facilities.



Product Name: D-Carb cement (CEM II A-LL 52.5 N)
Page: 4/7

Date of Issue: 28 May 2025 Rev. No.: 01

7.2. Conditions for safe storage, including any incompatibilities

Technical measures for safe

No special precautions.

storage:

Storage conditions: Store in closed original container in a dry place. Seal opened containers

and use up as soon as possible. When stored in humid conditions, the

chromate neutralisation will decrease.

7.3. Specific end use(s)

Specific use(s): Not relevant.

#### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1. Control parameters

Occupations	•				
Occupational exposure limits: CAS-No.: Chemical name:		Exposure limits:	Type:	Notes:	References:
1305-62-0	Calcium hydroxide	3 mg/m <sup>3</sup>	TWA	-	Melerences.
1303-02-0	Calcium nyaroxiae	5 mg/m	1 4 4 7		
471-34-1	Calcium Carbonate	10 mg/m <sup>3</sup>	TWA	-	
	Chromium (VI)	0.05 mg/m <sup>3</sup>	TWA	-	
N/A	compounds (as Cr)	3			
7778-18-9	Gypsum (Calcium	10 mg/m <sup>3</sup>	TWA	_	
7770-10-3	sulphate)	10 mg/m	1 7 7 7		
14808-60-7	Quartz (respirable	0.05 mg/m <sup>3</sup>	TWA	_	
14000 00 7	dust)	0.00 mg/m	1 7 7 7		
65997-15-1	Portland cement,	3 mg/m <sup>3</sup>	TWA		USECHH 2000
05997-15-1	Respirable dust	3 mg/m	IVVA	-	USECHII 2000
05007.45.4	<b>D</b> 4 1 4	40/3	T\A/A		LICECLIII 2000
65997-15-1	Portland cement,	10 mg/m <sup>3</sup>	TWA	-	USECHH 2000
	inhalable dust				

#### 8.2. Exposure controls

Engineering measures: Provide adequate ventilation. Observe occupational exposure limits and

minimise the risk of inhalation of dust.

Personal protection: Personal protection equipment should be chosen in discussion with the

supplier of the personal protective equipment.

Respiratory equipment: During dust-raising work: Use respiratory equipment with particle filter.

Hand protection: Wear protective gloves. Nitrile gloves are recommended. Other types of

gloves can be recommended by the glove supplier.

Eye protection: Wear goggles/face shield.

Skin protection: Wear special protective clothing. Hood or helmet shall be used in

connection with splashing work.

Hygiene measures: Remove contaminated clothing and wash the skin thoroughly with soap and

water after work.

**Environmental Exposure** 

Controls:

Not available.

# **C** aalborgportland

#### SAFETY DATA SHEET

Product Name: D-Carb cement (CEM II A-LL 52.5 N)

Page: 5/7

Date of Issue: 28 May 2025 Rev. No.: 01

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

9.1. Information on basic physical and chemical properties

Appearance: Cement white Odour: Odourless.

pH: Ready-to-use mixture: approx. 13

Boiling point:

Flash point:

Explosion limits:

Relative density:

Solubility:

Not relevant.

Not relevant.

Not relevant.

Miscible with water.

9.2. Other information

Other data: Not relevant.

#### **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity

Reactivity: None known.

10.2. Chemical stability

Stability: Stable under normal temperature conditions. The content of chromate

reducing agent is gradually diminished.

10.3 Possibility of hazardous reactions

Hazardous Reactions: None known.

10.4 Conditions to avoid

Conditions/materials to avoid: The product will harden into a hard mass in contact with water and

moisture.

10.5 Incompatible materials

Incompatible materials: Not known.

#### 10.6 Hazardous decomposition products

Hazardous decomposition products:

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

11.1. Information on toxicological effects

Inhalation: Dust may irritate throat and respiratory system and cause coughing.

Skin contact: Dust has an irritating effect on moist skin. Repeated or prolonged contact

with skin may cause allergic reactions in sensitive individuals.

Eye contact: Dust or splashes from the mixture may cause permanent eye damage.

Immediate first aid is necessary.

Ingestion: Not likely, due to the form of the product. Ingestion may cause severe

irritation of the mouth, the esophagus and the gastrointestinal tract.

Specific effects: Frequent inhalation of dust over a long period of time increases the risk of

developing lung diseases.



Product Name: D-Carb cement (CEM II A-LL 52.5 N) Page: 6/7

Date of Issue: 28 May 2025 Rev. No.: 01

#### **SECTION 12: ECOLOCAL INFORMATION**

12.1. Toxicity

Ecotoxicity: The product is not expected to be hazardous to the environment.

12.2. Persistence and degradability

Degradability: The product reacts with water to form a solid insoluble reaction product

which is non-degradable, according to information available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

12.4. Mobility in soil

Mobility: No data available.

12.5. Other adverse effects

Other adverse effects: None known.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste. Note that fully cured material is not considered as hazardous waste.

#### **SECTION 14: TRANSPORT INFORMATION**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

UN-No: None Allocated.

14.2. UN proper shipping name

Proper Shipping Name: None Allocated.

14.3. Transport hazard class(es)

Class: None Allocated.

14.4. Packing group

PG: None Allocated.

14.5. Environmental hazards

Marine pollutant: None Allocated.

**Environmentally Hazardous** 

substance:

14.6. Special precautions for user

Special precautions: None known.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk: Not relevant.



Product Name: D-Carb cement (CEM II A-LL 52.5 N) Page: 7/7

Date of Issue: 28 May 2025 Rev. No.: 01

#### **SECTION 15: REGULATORY INFORMATION**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special provisions: As a general rule, persons under 18 years of age are not allowed to work with this product. Users must be carefully instructed in the proper work

procedure, the dangerous properties of the product and the necessary safety

instructions.

#### 15.2. Chemical Safety Assessment

CSA status: Not relevant.

#### **SECTION 16: OTHER INFORMATION**

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions. The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.